

## Open-Top Sockets

TSOP Type I (Carrier Type)

Unit: mm

Part Number	Pin Count	Pitch	Actuation Force	Tip-Tip	Body Width	Package Length
OTS-28-0.55-02	28	0.55	1.4kg	13.4	11.8	8.2
OTS-32-0.5-03	32	0.5	1.4kg	20	18.4	8.2

TSOP Type I (Non-Carrier Type, One Point Contact)

Unit: mm

Part Number	Pin Count	Pitch	Actuation Force	Tip-Tip	Body Width	Package Length
OTS-28-0.55-03	28	0.55	1.4kg	13.4	11.8	8.2
OTS-32-0.5-01	32	0.5	1.5kg	14	12.4	8.2
OTS-32-0.5-08	32	0.5	1.2kg	20	18.4	8.2
OTS-40-0.5-01	40	0.5	2.0kg	20	18.4	10.2
OTS-48-0.5-01	48	0.5	1.2kg	20	18.4	12.2
OTS-56-0.5-01	56	0.5	1.5kg	20	8.4	14

TSOP Type I (Non-Carrier Type, Pinch Contact)

Unit: mm

Part Nuber	Pin Count	Pitch	Actuation Force	Tip-Tip	Body Width	Package Length
OTS-32-0.5-09	32	0.5	1.2kg	20	18.4	8.23
OTS-48-0.5-03	48	0.5	1.8kg	20	18.4	12
OTS-48-0.5-X	48	0.5	-	20	18.4	12.2
OTS-56-0.5-XX	56	0.5	-	20	18.4	14

TSOP Type II(Carrier Type)

Unit: mm

Part Number	Pin Count	Pitch	Actuation Force	Tip-Tip	Body Width	Package Length
OTS-20(26)-1.27-04	20	1.27	2.0kg	9.22	7.72	17.54
OTS-24(26)-1.27-04	24	1.27	2.0kg	9.22	7.72	17.54
OTS-26-1.27-04	26	1.27	2.0kg	9.22	7.72	17.54
OTS-24(32)-1.27-11	24	1.27	2.0kg	11.76	10.26	18.81
OTS-28(32)-1.27-11	28	1.27	2.0kg	11.76	10.26	18.81
OTS-32-1.27-11	32	1.27	2.0kg	11.76	10.26	21.35

TSOP Type II(Non-Carrier Type, Pinch Contact)

Unit: mm

Part Number	Pin Count	Pitch	Actuation Force	Tip-Tip	Body Width	Package Length
OTS-20(26)-1.27-14	20	1.27	1.0kg	9.4	7.77	17.44
OTS-24(26)-1.27-14	24	1.27	1.0kg	9.4	7.77	17.44
OTS-28-1.27-21	28	1.27	1.1kg	9.35	7.68	18.52
OTS-32-1.27-14	32	1.27	1.3kg	11.89	10.21	21.06
OTS-44-0.8-14	44	0.8	1.5kg	9.32	7.67	18.52
OTS-40(44)-0.8-09	40	0.8	1.4kg	11.89	10.21	18.54
OTS-44-0.8-09	44	0.8	1.5kg	11.89	10.21	18.54
OTS-40(50)-0.8-17	44	0.8	1.6kg	11.89	10.2	21.25
OTS-50-0.8-17	50	0.8	1.6kg	11.89	10.2	21.25
OTS-54-0.8-0.1	54	0.8	1.8kg	11.89	10.21	22.35
OTS-62-0.8-XX	62	0.8	-	15	13	25.75
OTS-88-0.65-01	88	0.65	3.0kg	18	16.4	29.5